

2 - 20" (50 - 500mm) diameters Keyway Milling Machine





- Induction hardened 'V' slides
- Quill type spindle direct drive
- Quick mounting chain system
- Optional auto feed available

A lightweight, portable 3 axis milling machine for the repair of keyways on shafts with 2 - 20" diameters.

The machine is supplied complete with toolkit including:

- Air filter lubricator (when required) and hose connection
- All required mounting bolts
- Storage / shipping box
- CE certificate
- Packing list
- Manual



Technical Details						
Maximum Stroke X	203mm	8"				
Maximum Stroke Y	50mm	2"				
Maximum Spindle Down Feed	50mm	2"				
Drive - Pneumatic	2.0 Hp	1.49 Kw				
Drive - Hydraulic	2.2 Hp	1.64 Kw				
Spindle R.P.M	Min: 50	Max: 640				
Hydraulic Supply @ 1050 psi (70 bar)	50 L/min	13 Gal/min				
Air Consumption / Supply Required	98 s.c.f.m	2.69 m3/m				

Feed Rates		
Hand Feed	2mm/rev	0.078"/rev

Weights and Dimensions		
Machine Weight (including base 15Kg)	95 Kgs	209 Lbs
Shipping Weight	126 Kgs	278 Lbs

Shipping Dimensions								
Length		Width		Height				
mm	inches	mm	inches	mm	inches			
950	37	480	19	630	25			

